<u>ABBREVIATIONS</u> AMERICAN CONCRETE INSTITUTE __AMERICAN INSTITUTE OF STEEL MASONRY MAXIMUM CONSTRUCTION MECHANICAL ARCHITECT OR ARCHITECTURAL AMERICAN SOCIETY OF CIVIL MILES PER HOUR FNGINFERS NATIONAL CONCRETE MASONRY AMERICAN STANDARDS FOR ASSOCIATION TESTING AND MATERIALS ON CENTER AMERICAN WELDING SOCIETY OCCUPATION SAFETY AND HEALTH ADMINISTRATION **BOTTOM OF** BEARING PRESTRESSED CONCRETE CENTERLINE POUNDS PER SQUARE INCH DEPARTMENT OF NATURAL POUNDS PER SQUARE FOOT RESOURCES __ PRE-ENGINEERED METAL DRAWINGS EACH FACE STEEL DECK INSTITUTE **ELECTRICAL** ELEVATION STEEL JOIST INSTITUTE **EACH WAY** _____STRUCTURAI EXPANSION TRUSS PLATE INSTITUTE TYPICAL (SITUATION OCCUR HORIZONTAL INTERNATIONAL BUILDING CODE **UNLESS NOTED OTHERWISE** INSIDE FACE

GENERAL CONDITIONS:

1. IF ANY GENERAL NOTE CONFLICTS WITH ANY DETAIL OR NOTE ON THE PLANS OR IN THE SPECIFICATIONS, THE STRICTEST PROVISION SHALL GOVERN.

UNLESS OTHERWISE NOTED

VERTICAL

VERIFY IN FIELD

2. THE STRUCTURAL DRAWINGS ARE FOR THE PLACEMENT AND SIZE OF STRUCTURAL COMPONENTS ONLY. REQUIREMENTS MADE BY OSHA, DNR, AND ALL APPLICABLE SAFETY CODES ARE TO BE DETERMINED AND PROVIDED BY THE CONTRACTOR.

KILOPOUNDS

LONG LEG VERTICAL

LONG LEG HORIZONTAL

- 3. THE STRUCTURE IS DESIGNED TO BE SELF-SUPPORTING AND STABLE AFTER IT IS FULLY COMPLETED ACCORDING TO THE PLANS AND SPECIFICATIONS. IT IS THE CONTRACTOR'S SOLE RESPONSIBILITY TO DETERMINE CONSTRUCTION/ERECTION PROCEDURE AND SEQUENCE, AND TO ENSURE THE SAFETY OF THE STRUCTURE AND ITS COMPONENT PARTS DURING CONSTRUCTION. THIS INCLUDES PROVIDING TEMPORARY BRACING, SHORING, GUYS OR TIE-DOWNS. THESE TEMPORARY SUPPORTS SHALL REMAIN IN PLACE UNTIL ALL STRUCTURAL COMPONENTS ARE IN PLACE AND COMPLETED AS THE STRUCTURAL MEMBERS OR SYSTEMS ARE NOT SELF-BRACING UNTIL PERMANENTLY CONNECTED TO THE STRUCTURE. DEFERRED SUBMITTALS
- COMPONENTS OF THE PROJECT DESIGNED BY THE CONTRACTOR'S SPECIALTY ENGINEER WHICH REQUIRE PRODUCT OR SYSTEM ENGINEERING, SEALED SHOP DRAWINGS AND CALCULATIONS TO BE SUBMITTED FOR REVIEW BY THE DESIGN PROFESSIONAL OF RECORD AND TO THE BUILDING OFFICIAL ARE AS FOLLOWS:
- COLD-FORMED METAL FRAMING
- PRECAST CONCRETE FRAMING PRODUCTS
- CURTAIN WALL SYSTEMS PRE-ENGINEERED CANOPIES
- 5. THE ARCHITECT AND STRUCTURAL ENGINEER ASSUME NO LIABILITY FOR THE STRUCTURE DURING CONSTRUCTION. AS SUCH, THE MEANS AND METHODS OF CONSTRUCTION ARE THE SOLE RESPONSIBILITY OF THE CONTRACTOR(S).
- 6. USE OF ENGINEERING DRAWINGS AS ERECTION DRAWINGS BY THE CONTRACTOR IS EXPRESSLY PROHIBITED. 7. DIMENSIONS ON STRUCTURAL DRAWINGS ARE TO BE CHECKED AGAINST ARCHITECTURAL, MECHANICAL AND ELECTRICAL DRAWINGS AS WELL AS AGAINST EXISTING FIELD CONDITIONS BY
- 8. THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING THE LOCATION AND PLACEMENT OF INSERTS, HANGERS, SLEEVES, DUCTWORK, PADS AND ANCHOR RODS THAT ARE REQUIRED BY MECHANICAL EQUIPMENT.
- SHOP DRAWINGS, FABRICATION DETAILS, PRODUCT LITERATURE AND CERTIFICATES SHALL BE SUBMITTED BEARING THE CONTRACTOR'S REVIEW STAMP FOR THE FOLLOWING STRUCTURAL SYSTEMS. FAILURE OF THE CONTRACTOR TO REVIEW AND STAMP SUBMITTALS PRIOR TO FORWARDING THEM TO THE DESIGN PROFESSIONAL(S) FOR REVIEW SHALL CONSTITUTE GROUNDS FOR REJECTION. USE OF THESE ENGINEERING DRAWINGS, PLANS OR DETAILS USED AS ERECTION PLANS OR SHOP DRAWINGS BY THE CONTRACTOR IS EXPRESSLY PROHIBITED. SUBMITTALS BEARING IMAGES ELECTRONICALLY COPIED FROM THE ENGINEERING DRAWINGS WILL BE
- CONCRETE COMPONENTS, MIX DESIGNS AND CONCRETE REINFORCEMENT
- PRECAST CONCRETE FRAMING PRODUCTS
- MASONRY COMPONENTS AND REINFORCEMENT STRUCTURAL STEEL, METAL DECK AND METAL FABRICATIONS
- OPEN WEB / LONG-SPAN JOISTS AND JOIST GIRDERS INCLUDING CHORD AND WEB MEMBER
- COLD-FORMED METAL FRAMING

9. SHOP DRAWING SUBMITTALS

- CURTAIN WALL SYSTEMS
- PRE-ENGINEERED CANOPIES
- HANDRAILS AND GUARDRAILS

MASONRY

REQUIRED INSPECTIONS COORDINATE CONSTRUCTION SCHEDULE WITH OWNER'S QUALITY INSPECTOR WITH ADEQUATE NOTICE PROVIDED IN ORDER TO ALLOW THE FOLLOWING INSPECTIONS. SEE PROJECT MANUAL AND

REFERENCED CODES FOR SPECIFIC INSPECTION AND TESTING REQUIREMENTS.

- SOIL BEARING CAPACITY
- SUB-GRADE PREPARATION AND FILL COMPACTION CONCRETE PRECAST CONCRETE FRAMING PRODUCTS
- WELDING AND HIGH STRENGTH BOLTING ROOF AND FLOOR DIAPHRAGM (METAL DECK) CONNECTIONS

DESIGN LOADS

CATEGORY	GOCCUPANCY CATEGORY (1604.5):C	EGORY II
MINIMUM 20 PS	'E LOAD (1603.1.1):MINI	M 20 PSF
	VE LOAD (1603.1.1):	~~~
Pg = 125 PSF	HT STORAGE, Pg = 1:	SF
Pg = 100 PSF		
Da - 20 DSE	OW LOAD (1603.1.3 & 1608):	ee.
Pg = 30 PSF	OUND SNOW LOAD, Pg = : POSURE,	SF (
Df = 21 DSF	POSURE, T ROOF SNOW LOAD, Pf = 2	`
11-21101 Ce = 1_0	OW EXPOSURE FACTOR	01
Is = 1 .0	DW EXPOSURE FACTOR, Ce DW LOAD IMPORTANCE FACTOR, Is	.0
Ct = 1 . 0	ERMAL FACTOR, CI	.0
107 MPH	AD: BASED ON ACSE 7-16 (1603.1.4 & 1609): BIC WIND SPEED =10	PH
С	ND EXPOSURE =	С
T/- U .33	ERNAL PRESSURE COEFFICIENT - +	.00
23.33 PSF	FRS PEAK VELOCITY PRESSURE = 23.3	SF
	IMATE COMPONENTS AND CLADDING PRESSURE:	
42.9 PSF (ZONE	ROOF (100 S.F.) =42.9	(ZONE 1
54.1 PSF (ZONE	ROOF (100 S.F.) =54.1	(ZONE 2
54.1 PSF (ZONE	ROOF (100 S.F.) =	(ZONE 3
31.2 PSF (ZONE	WALLS (50 S.F.) =	(ZONE 4
31.2 PSF (ZONE	WALLS (50 S.F.) =31.2	(ZONE 5
	JAKE DESIGN DATA (1603.3.1.5 & 1613):	
le = 1. 00		00
	PPED SPECTRAL RESPONSE ACCELERATIONS	
Ss = 0. 093		
91 = 0.046	S1 =	0 046 a

2. MAPPED SPECTRAL RESPONSE ACCELERA	ATIONS	
	Ss=	0.093 g
	S1 =	0. 046 g
3. SITE CLASS =		D
4. SPECTRAL RESPONSE COEFFICIENTS		
	SDs =	0. 099 g
	SD1 =	0. 074 g
SEISMIC DESIGN CATEGORY =		В
2 DAGIO GEIGLAIG EGDOE DEGIGENIA ON GEEL		
BASIC SEISMIC-FORCE-RESISTING SYSTEM	/IS:	
	/IS: ECAST CONCRETE S	HEAR WALLS
ORDINARY PRE	·	HEAR WALLS
	·	HEAR WALLS
ORDINARY PRE 7. SEISMIC RESPONSE COEFFICIENTS (Cs):	·	
ORDINARY PRE 7. SEISMIC RESPONSE COEFFICIENTS (Cs): PRECAST CONCRETE SHEAR WALL	·	

BUILDING A.9: 62.2 KIPS 10. ANALYSIS PROCEDURE USED: EQUIVALENT LATERAL FORCE PER ASCE 7, SECTION 12.8

BUILDING A.5, A.6: 62.4 KIPS ~~~~

BUILDING A.7. A.8 (BURLINGTON): 37.7 KIF

1. THIS STRUCTURE IS NOT LOCATED IN A FLOOD HAZARD AREA.

THE CENTERLINE OF FOOTING IS ALSO THE CENTERLINE OF COLUMN.

- 1. REFER TO ROOF FRAMING PLANS FOR MECHANICAL EQUIPMENT LOADS. 1. BY ITS SEISMIC DESIGN CATEGORY B, THIS STRUCTURE HAS NO REQUIREMENT FOR SYSTEMS AND COMPONENTS REQUIRING SPECIAL INSPECTIONS FOR SEISMIC
- <u>03 00 01 FOUNDATIONS</u> 1. FOOTINGS SHALL BEAR ON FIRM, UNDISTURBED SOIL OR ENGINEERED FILL WITH AN ASSUMED
- SAFE ALLOWABLE NET SOIL PRESSURE OF 1,500 PSF IN ACCORDANCE WITH THE GEOTECHNICAL INVESTIGATION REPORT PREPARED BY PEA, INC., PROJECT No. 2019-422 (DATED FEBRUARY 19, 2020). IF SOIL OF THIS CAPACITY IS NOT FOUND AT THE ELEVATIONS INDICATED, FOOTINGS SHALL BE ENLARGED OR LOWERED AT THE DIRECTION OF THE ARCHITECT/ENGINEER. 2. UNLESS OTHERWISE NOTED OR DETAILED, ALL FOUNDATIONS SHALL BE LOCATED SUCH THAT
- PREPARATION OF THE SITE, BUILDING FOOTPRINT AND SLAB SUB-BASE SHALL PROCEED IN COMPLIANCE WITH LOCAL CODES AND THE PROJECT SOILS REPORT IDENTIFIED ABOVE. UNLESS OTHERWISE NOTED OR SPECIFIED, ALL FILL UNDER FLOOR SLABS AND BEHIND FOUNDATION WALLS SHALL BE COMPACTED WITH VIBRATORS, COMPACTORS, ETC. TO 95% MAXIMUM DENSITY (MODIFIED PROCTOR) AT OPTIMUM MOISTURE CONTENT. 4. PROVIDE NECESSARY SHEETING, SHORING, FORMING OR BRACING, ETC., DURING EXCAVATION AS REQUIRED TO PROTECT SIDES OF EXCAVATIONS OR AS REQUIRED TO COMPLY WITH SAFETY REGULATIONS. DO NOT BACKFILL BEHIND BASEMENT WALLS UNTIL FLOOR FRAMING OR
- TEMPORARY BRACING IS IN PLACE. 5. THIS TRADE SHALL PROVIDE PUMPS, WELL POINTS, OR OTHER SYSTEMS AS REQUIRED BY THE CONDITIONS IDENTIFIED IN THE PROJECT SOILS REPORT. PUMPS SHALL BE OPERATED AS REQUIRED TO ACCOMPLISH THE ABOVE, ON A 24-HOUR BASIS, IF NECESSARY. UNDER NO CONDITION SHALL WATER BE ALLOWED TO WASH OVER FRESHLY PLACED CONCRETE.
- 6. ALL BOTTOM OF FOOTING TRANSITIONS SHALL BE MADE USING STEPS AS SHOWN IN TYPICAL FOOTING STEP DETAIL. WHERE NEW FOOTINGS ABUT EXISTING FOUNDATIONS, CAREFULLY HAND EXCAVATE AND PLACE BOTTOM OF NEW FOOTING AT THE SAME ELEVATION AS THE

03 00 02 - CONCRETE

SUPER-PLASTICIZER

- 1. THE CONCRETE PORTIONS OF THIS STRUCTURE ARE DESIGNED ACCORDING TO THE LATEST ULTIMATE STRENGTH DESIGN PROVISIONS OF THE AMERICAN CONCRETE INSTITUTE BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE AND COMMENTARY (ACI 318) INCLUDING SECTIONS 1902 THRU 1908 OF CHAPTER 19 IN THE INTERNATIONAL BUILDING CODE. CONCRETE COMPONENTS HAVE BEEN DESIGNED ACCORDING TO THE PROVISIONS FOR SEISMIC DESIGN
- 2. ALL CONCRETE SHALL BE NORMAL WEIGHT (150 PCF). MINIMUM CONCRETE STRENGTH SHALL BE f'c = 3,000 PSI MIN. AT 28 DAYS, UNLESS NOTED OTHERWISE; SUPPORTED SLABS AND SLABS ON GRADE SHALL BE f'c=3500 PSI MIN. UNLESS NOTED OTHERWISE. PROVIDE f'c = 4,000 PSI WITH
- 6% +/- 1% ENTRAINED AIR WHERE CONCRETE IS EXPOSED TO EXTERIOR ATMOSPHERE OR 3. ALL CONCRETE SHALL BE PORTLAND CEMENT CONFORMING TO ASTM C150. AGGREGATE SHALL
- 4. ADMIXTURES SHALL BE USED TO FACILITATE CONCRETE PLACEMENT. AID DIFFICULT PLACING CONDITIONS OR ASSIST IN ATTAINING SPECIFIED CONCRETE QUALITIES. ADMIXTURES SHALL HAVE LESS THAN 0.05 PERCENT CHLORIDE IONS. AIR ENTRAINMENT PER ASTM C260
 - WATER REDUCER PER ASTM C494, TYPE A WATER REDUCER/ACCELERATOR PER ASTM C494, TYPE C OR E WATER REDUCER/RETARDER _ PER ASTM C494, TYPE B OR TYPE D
- 5. CONCRETE MIXES SHALL BE PROPORTIONED PER SECTION 3.9 OF ACI-301. CERTIFIED HISTORICAL TEST DATA SHALL SERVE AS A BASIS FOR EACH MIX DESIGN. DEVIATIONS SHALL BE SUBSTANTIATED WITH ADDITIONAL CERTIFIED TRIAL MIX TESTING AND RESULTS. SUBMIT MIX DESIGN. HISTORICAL TEST DATA OR TRIAL MIX RESULTS FOR APPROVAL PRIOR TO PROCEEDING WITH THE WORK. WHERE HISTORICAL TEST DATA IS NON-EXISTENT THE FOLLOWING GUIDELINES SHALL APPLY:

PER ASTM C494, TYPE F OR G

TYPE	COMPRESSIVE STRENGTH, fc (28 DAY, PSI)	CEMENT CONTENT (LBS/C.Y.)	WATER / CEMENT RATIO (BY WEIGHT)	SLUMP
STANDARD, NORMAL WT.	3,000 M I N.	470 M I N.	0.52 MAX.	4" MAX
STANDARD, NORMAL WT.	3,500 M I N.	517 M I N.	0.50 MAX	4" MAX.
AIR ENTR., NORMAL WT.	4,000 M I N.	564 M I N.	0.40 MAX	4" MAX
STANDARD, LIGHT WT.	3,500 M I N.	564 M I N.	0.44 MAX.	SEE SPEC.

- 6. ALL CONCRETE WORK AND PLACEMENT SHALL CONFORM TO THE LATEST ACI STANDARDS AND RECOMMENDATIONS. FREE FALL SHALL NOT EXCEED 10 FEET FOR ALL CONCRETE CONTAINING HIGH-RANGE WATER REDUCER (SUPER-PLASTICIZER) AND 5 FEET FOR ALL OTHER CONCRETE PROVIDE ELEPHANT TRUNK, TREMIES OR OTHER PLACING EQUIPMENT OR OPENINGS IN SIDES OF FORMS AS REQUIRED TO LIMIT FREE FALL
- 7. ALL REINFORCING BARS. DOWELS AND TIES SHALL CONFORM TO ASTM A615. GRADE 60. ALL REINFORCING STEEL SHALL BE CONTINUOUS AND SHALL HAVE 36 BAR DIAMETER LAP (MIN.) AND SHALL BE FABRICATED AND PLACED IN ACCORDANCE WITH ACI 315 AND ACI 318, LATEST EDITION. HOOK ALL BEAM BARS AT DISCONTINUOUS ENDS.
- 8. ALL WELDED WIRE FABRIC SHALL CONFORM TO ASTM A185 FURNISHED IN FLAT MATS OR SHEETS, NOT IN ROLLS. PROVIDE MINIMUM 8" LAP BETWEEN SHEETS. ALL SLAB REINFORCING SHALL BE SUPPORTED ON SAND CHAIRS. 9. ALL COLUMN REINFORCING SPLICES SHALL BE 24 BAR DIAMETERS. ALL COLUMN/PIER OR WALL

SHALL BE MINIMUM 30 BAR DIAMETERS. PROVIDE 2-#5 BARS TOP AND BOTTOM AND EACH SIDE

- DOWELS SHALL BE 48 DIAMETERS LONG USING THE SAME SIZE AND QUANTITY AS THE VERTICAL COLUMN/PIER OR WALL BARS. PROVIDE HOOKS AS REQUIRED FOR PLACEMENT. 10. REINFORCED CONCRETE WALLS AND WALL FOOTINGS SHALL HAVE CORNER BARS AT EACH INTERSECTION OF THE SAME SIZE AND SPACING AS THE MAIN HORIZONTAL REINFORCING. LAPS
- OF ALL OPENINGS AND 2-#5 x 4'-0" DIAGONAL BARS AT CORNERS OF OPENINGS. PROVIDE 2-#5 BARS TOP AND BOTTOM IN SLABS AT ALL RE-ENTRANT (INSIDE) CORNERS. 11. ALL EXPOSED CONCRETE CORNERS AND EDGES SHALL BE CHAMFERED 3/4".
- 03 40 00 PRECAST CONCRETE FRAMING PRODUCTS:

I. PRECAST CONCRETE WALL PANELS SHALL BE DESIGNED BY THE PRECAST CONCRETE PRODUCT SUPPLIER. SHOP DRAWINGS AND CALCULATIONS SHALL BE PREPARED BY AND SUBMITTED BEARING THE SEAL OF A PROFESSIONAL ENGINEER REGISTERED IN THE STATE OF MICHIGAN. AS A MINIMUM, THE LOADING GIVEN BELOW SHALL BE USED. ADDITIONAL LOADING OR LOAD COMBINATIONS IF REQUIRED BY CODE SHALL BE DETERMINED AND IMPLEMENTED BY THE PRECAST CONCRETE

2. THE PRECAST CONCRETE PRODUCT SUPPLIER SHALL BE A MEMBER OF THE PRESTRESSED CONCRETE INSTITUTE (PCI). THE DESIGN AND MANUFACTURE OF ALL PRECAST CONCRETE PRODUCTS SHALL CONFORM TO ALL PROVISIONS OF THE "PCI DESIGN HANDBOOK" AND TO THE LATEST ACI STANDARDS AND GUIDELINES.

3. THE PRECAST CONCRETE SUPPLIER SHALL COORDINATE THE SIZE, LOAD AND LOCATION OF ALL MECHANICAL UNITS WITH THE GENERAL AND MECHANICAL CONTRACTORS. 4. THE PRECAST CONCRETE SUPPLIER SHALL COORDINATE THE LOCATION OF ALL FRAMING MEMBERS TO BE CARRIED BY THE PRECAST CONCRETE UNITS, INCLUDING THE LOCATION OF

5. ALL HOLES IN PRECAST CONCRETE WALL PANELS ARE TO BE CORE DRILLED. PROVIDE THE THE LOCATION OF ALL REQUIRED HOLES TO THE PRECAST CONCRETE SUPPLIER TO CONFIRM STRUCTURAL ADEQUACY

EMBEDDED PLATES, ANCHORS, TEMPORARY BEAMS, COLUMNS, ETC

6. DESIGN LOADS ROOF DEAD: 25 PSF

DEFLECTION LIMITATIONS: SPAN/360

ROOF LIVE: SEE ABOVE TOTAL: AS A MINIMUM REFER TO SCHEDULE ON SHEET S-104, S-105, AND S-106 SEISMIC: SEE ABOVE

MAIN WINDFORCE RESISTING SYSTEM WIND: SEE ABOVE (AS A MINIMUM, WIND PARALLEL TO THE WALL SHALL BE AS SCHEDULED ON SHEET S-104, S-105, AND S-106) COMPONENTS AND CLADDING WIND LOAD

PER CURRENT MICHIGAN BUILDING CODE WITH BASIC WIND SPEED = SEE ABOVE (AS A MINIMUM, WIND PERPENDICULAR TO THE WALL SHALL NOT BE LESS THAN = 29.5 PSF) PRECAST WALL PANEL SELF WEIGHT LIMIT = LESS THAN OR EQUAL TO 80 PSF

05 00 01 - STRUCTURAL STEEL

- 1. THE STRUCTURAL STEEL PORTIONS OF THIS STRUCTURE ARE DESIGNED ACCORDING TO THE ALLOWABLE STRESS DESIGN PROVISIONS OF THE 9TH EDITION OF THE AISC MANUAL OF STEEL CONSTRUCTION. THE LOAD AND RESISTANCE FACTOR DESIGN PROVISIONS OF THE 2ND EDITION AISC MANUAL OF STEEL CONSTRUCTION INCLUDING CHAPTER 22 IN THE CURRENT BUILDING CODE. STEEL COMPONENTS HAVE BEEN DESIGNED ACCORDING TO THE PROVISIONS FOR
- SEISMIC DESIGN CATEGORY B. COMPLECTION ALLOWANCE SHALL BE CREDITED TO THE 2. STEEL DETAILING, FABRICATION AND ERECTION SHALL BE IN ACCORDANCE WITH THE LATEST AISC SPECIFICATIONS FOR "STRUCTURAL STEEL BUILDINGS".
- 3. ALL STRUCTURAL STEEL SHALL CONFORM TO THE LATEST ASTM SPECIFICATIONS ACCORDING TO THE FOLLOWING SERIAL DESIGNATIONS BY SHAPE:
- WIDE FLANGES:__ _ A992 OR ASTM A572, Fy=50 KSI ANGLES, TEES, BARS AND PLATES:
- SQUARE OR RECTANGULAR HOLLOW STRUCTURAL SHAPES OR TUBES:___
- ASTM A500, GR, B, Fy=46 KSI ROUND HOLLOW STRUCTURAL SHAPES OR PIPES: GRADE B,___ Fy=35 KSI
- 4. ALL WELDED CONNECTIONS SHALL CONFORM TO THE LATEST AWS CODE, USING E70XX ELECTRODES, WITH WELDING PERFORMED BY QUALIFIED WELDERS. 5. BOLTED CONNECTIONS SHALL BE MADE WITH A325-N OR A490-N BOLTS. LOCATIONS OF SLIF CRITICAL CONNECTIONS SHALL BE AS NOTED ON THE DRAWINGS, IF REQUIRED. ALL BOLTS ARE TO BE INSTALLED IN ACCORDANCE WITH THE LATEST AISC SPECIFICATIONS FOR "STRUCTURAL JOINTS USING ASTM A325 OR A490 BOLTS".
- 6. THE DESIGN, CONFIGURATION, ERECTION SAFETY AND SEQUENCING OF ALL STRUCTURAL STEEL CONNECTIONS SHALL BE THE RESPONSIBILITY OF THE STRUCTURAL STEEL FABRICATOR. REVIEW AND ACCEPTANCE OF THE SHOP DRAWINGS BY THE ENGINEER SHALL CONSTITUTE APPROVAL OF THE LOAD CARRYING ADEQUACY ONLY. 7. CONNECTIONS SHALL BE DESIGNED FOR ONE-HALF THE TOTAL ALLOWABLE UNIFORM LOAD (MIN.) PER AISC BEAM LOAD TABLES, UNLESS NOTED OTHERWISE.
- 8. TEMPORARY ERECTION SEATS SHALL BE PROVIDED AS RECOMMENDED ON PAGE 3-59 OF THE LATEST EDITION AISC PUBLICATION "ENGINEERING FOR STEEL CONSTRUCTION". 9. <u>ALL STEEL LINTELS IN EXTERIOR MASONRY WALL CONSTRUCTION AND ALL OTHER EXPOSED</u> STEEL SHALL BE GALVAN**I**ZED.
- 10. THE DESIGN OF STEEL FRAMED STAIRS SHALL BE THE RESPONSIBILITY OF THE STEEL FABRICATOR PROVIDE COMPLETE ENGINEERED STAIR ASSEMBLIES CONFORMING TO THE ARCHITECTURAL INTENT, UNDER THE SEAL OF AN ENGINEER REGISTERED IN THE STATE OF λ \langle MICHIGAN. INCLUDING METAL FRAMING. HANGERS. MASONRY BEARING PLATES. COLUMNS AND TAILING ASSEMBLIES, AND OTHER COMPONENTS NECESSARY TO SUPPORT THE STAIRS AND LANDINGS INCLUDING ANCHORAGE TO THE SUPPORTING STRUCTURE.

11. DRILLED-IN ANCHORS SHALL BE EITHER "EXPANSION" OR "ADHESIVE" AS INDICATED ON THE

- DRAWINGS. INSTALLATION OF DRILLED-IN ANCHORS SHALL BE IN COMPLIANCE WITH MANUFACTURER'S LITERATURE AND GUIDELINES. EXPANSION BOLTS SHALL BE "HILTI KWIK BOLT III" OR APPROVED EQUAL. ADHESIVE SHALL BE "HILTI HIT HY-200" OR APPROVED EQUAL. 12. REFER TO ARCHITECTURAL DRAWINGS FOR ADDITIONAL ANGLES, PLATES, BARS, CLIPS, ETC. ATTACHED TO STRUCTURAL STEEL. VERIFY EXACT SIZE AND LOCATION OF ALL FLOOR AND ROOF OPENINGS WITH CONTRACTOR INVOLVED. IN ADDITION TO L5x3 1/2x5/16 (L.L.V.) PERIMETER CURB SUPPORT FRAMES. PROVIDE L3x3x1/4 FRAMES AT OPENINGS UNDER MECHANICAL UNITS TO SUPPORT METAL DECK. FAILURE TO CONSULT ALL DRAWINGS FOR
- REQUIRED STEEL SHALL NOT CONSTITUTE A BASIS FOR EXTRAS. 13. THIS STEEL FRAME IS NON SELF-SUPPORTING PER AISC "CODE OF STANDARD PRACTICE", SECTIONS 7.9.3. AND 7.9.5.; ERECTION, BRACING, SHORING, ETC. SHALL CONFORM TO THESE SECTIONS. IT IS THE CONTRACTOR'S SOLE RESPONSIBILITY TO DETERMINE ERECTION 14. ALL STEEL EXPOSED TO THE WEATHER CONDITIONS SHALL HAVE ZINC RICH PRIMER TOUCH UP
- AFTER ALL CONNECTIONS HAVE BEEN COMPLETED AND INSPECTED. 05 00 02 - STEEL JOISTS/JOIST GIRDERS

1. STEEL JOISTS AND JOIST GIRDERS ARE TO BE FABRICATED BY A MEMBER OF THE STEEL JOIST INSTITUTE AND BE DESIGNED, FABRICATED AND ERECTED IN ACCORDANCE WITH THE LATEST SJI SPECIFICATIONS AND RECOMMENDATIONS. JOISTS SHALL BE DESIGNED FOR A MINIMUM NET UPLIFT OF 10 PSF. UPLIFT BRIDGING SHALL BE PROVIDED AS REQUIRED.

- 2. ALL PROVISIONS OF THE "RECOMMENDED CODE OF STANDARD PRACTICE FOR STEEL JOISTS AND JOIST GIRDERS" AS ADOPTED BY THE SJI SHALL BE ADHERED TO. 3. JOIST AND WEB GEOMETRY INCLUDING SIZES SHALL BE SUBMITTED TO THE ENGINEER FOR PROJECT RECORD. 4. STEEL JOISTS BEARING ON STEEL BEAMS OR PLATES, ARE TO BE CONNECTED WITH MINIMUM 2-INCH LONG, 1/8-INCH FILLET WELD EACH SIDE OF BEARING. EXTEND BOTTOM CHORDS OF JOISTS AT COLUMNS TO A STABILIZER PLATE. DO NOT CONNECT UNLESS NOTED OTHERWISE. IF NO JOIST OCCURS DIRECTLY AT A COLUMN, EXTEND BOTTOM CHORDS OF EACH ADJACENT
- 5. ALL STEEL JOISTS/JOIST GIRDERS EXPOSED TO THE WEATHER CONDITIONS SHALL HAVE ZINC RICH PRIMER TOUCH UP AFTER ALL CONNECTIONS HAVE BEEN COMPLETED AND INSPECTED.

05 00 03 - METAL DECK AND FORM

JOIST TO A STABILIZER PLATE.

CONT. L3x3x1/4 W/ 3/4" DIA.

- ROOF BEAM, SEE PLAN FOR

SIZE AND SPACING

SEE FOUNDATION PLAN

WALL REINFORCING _

KEYNOTES FOR MASONRY

Typical Beam Bearing

- STEEL BEAM AND PLATE

LINTEL, AS SCHEDULED

WATERPROOFING AND

FLASHING REQUIREMENTS

GROUT (3) COURSES SOLID

UNDER LINTEL BEARING AS

PROVIDE (2) VERT, BARS AT JAMBS UNDER LINTEL

BEARING AS SPECIFIED IN

SPECIFIED

KEYED NOTE

Control Joint at Steel Lintels

3/4" = 1'-0"

SEE ARCH FOR

EXPANSION BOLTS AT 32" O.C. _

- METAL DECK AND FORM SHALL CONFORM TO ALL PROVISIONS OF THE "CODE OF RECOMMENDED STANDARD PRACTICE FOR COMPOSITE DECK, FORM DECK, AND ROOF DECK CONSTRUCTION" AS ADOPTED BY THE STEEL DECK INSTITUTE. 2. METAL DECK AND FORM SHALL BE PROVIDED WITH NESTING SIDE SEAMS OF DEPTH AND GAGE
- AS INDICATED ON THE DRAWINGS. METAL ROOF DECK SHALL BE WIDE RIB TYPE "B". PROVIDE DECK MANUFACTURER'S STANDARD ROOF SUMP PANS FOR EACH ROOF SUMP LOCATION. 3. METAL DECK AND FORM IS DESIGNED TO ACT AS A DIAPHRAGM AND IS INTENDED TO BRACE THE
- BUILDING. EXTREME CARE SHALL BE UTILIZED TO INSTALL DECK AND FORM CONNECTIONS. 4. CONNECTIONS: 1 1/2" METAL ROOF DECK: CONNECT TO ALL SUPPORTING STEEL AS REQUIRED TO DEVELOP
- 451 POUNDS PER LINEAR FOOT HORIZONTAL DECK SHEAR CAPACITY IN STRICT ACCORDANCE WITH THE METHODS PRESCRIBED BY THE STEEL DECK INSTITUTE (SDI). MECHANICAL CONNECTIONS SHALL BE MADE USING HILTI X-HSN 24 PINS WITH 36/7 PATTERN AT ALL SUPPORTS ACCORDING TO DECK CONNECTION KEY PLAN. 36/5 ELSEWHERE: PROVIDE SIDELAP CONNECTORS PER DECK SPAN PLUS ONE AT EACH SUPPORT USING #10 HILTI DRILL SCREWS. WELDED CONNECTIONS SHALL BE MADE USING 5/8" DIAMETER PUDDLE WELDS WITH 36/7 PATTERN AT ALL SUPPORTS ACCORDING TO DECK CONNECTION KEY PLAN, 36/5 ELSEWHERE; PROVIDE 3 SIDELAP CONNECTORS PER DECK SPAN PLUS ONE AT EACH SUPPORT USING #10 SELF-DRILLING SCREWS. REFER TO SPECIFICATIONS FOR ADDITIONAL ERECTION PROCEDURES. SELECTED CONNECTION METHOD SHALL BE INDICATED ON DECK SHOP DRAWINGS INCLUDING MECHANICAL MANUFACTURER'S SUPPORTING PRODUCT LITERATURE. 0.6" FORM DECK: CONNECT TO SUPPORTING CFMF JOISTS WITH #12 SEFL-DRILLING SCREWS

AT 6" O.C. AT SHEET ENDS AND 12" O.C. AT INTERMEDIATE SUPPORTS.

05 00 04 - COLD-FORMED METAL FRAMING - (CFMF) PRODUCTS

- THE COLD-FORMED METAL FRAMING PORTIONS OF THIS STRUCTURE ARE DESIGNED ACCORDING TO THE ALLOWABLE STRESS DESIGN PROVISIONS OF THE LATEST EDITION OF THE AISI SPECIFICATION FOR THE DESIGN OF COLD-FORMED STEEL STRUCTURAL MEMBERS INCLUDING SECTIONS 2205 AND 2211 OF CHAPTER 22 IN THE CURRENT BUILDING CODE. CFMF METAL COMPONENTS HAVE BEEN DESIGNED ACCORDING TO THE PROVISIONS FOR SEISMIC DESIGN CATEGORY B. 2. COLD-FORMED METAL FRAMING AND CONNECTIONS SHALL BE DESIGNED BY THE METAL PRODUCT MANUFACTURER. SHOP DRAWINGS AND CALCULATIONS SHALL BE PREPARED BY AND SUBMITTED BEARING THE SEAL OF A PROFESSIONAL ENGINEER REGISTERED IN THE STATE OF MICHIGAN. AS A /A
- COMBINATIONS IF REQUIRED BY CODE SHALL BE DETERMINED AND IMPLEMENTED BY THE COLD-FORMED METAL FRAMING DESIGNER. 3. MINIMUM STANDARD DESIGN THICKNESSES INDICATED ON THE DRAWINGS SHALL BE INTERPRETED AS THE FOLLOWING:

MINIMUM, THE LOADING GIVEN BELOW SHALL BE USED. ADDITIONAL LOADING OR LOAD

43 = 0.0451 INCH 54 = 0.0566 INCH 68 = 0.0713 INCH

4. ALL COLD-FORMED METAL FRAMING SHALL CONFORM TO ASTM A446. GRADE D (MINIMUM Fv = 50 KSI) FOR 43 OR HEAVIER AND ASTM A446, GRADE A (MINIMUM Fy=33 KSI) FOR 33 OR LIGHTER. UNLES NOTED OTHERWISE, ALL FRAMING TO BE GALVANIZED IN ACCORDANCE WITH ASTM A525 G60 COATING; STUDS SUPPORTING MASONRY SHALL BE GALVANIZED WITH ASTM A525 G90 COATING. 5. COLD-FORMED METAL FRAMING SIZES INDICATED ON THE DRAWINGS ARE MINIMUM AND SHALL BE USED FOR BIDDING PURPOSES ONLY. FINAL SIZES SHALL BE DETERMINED AND PROVIDED IN CONJUNCTION WITH THE METAL PRODUCT MANUFACTURER'S STANDARD SHAPES, SIZES AND DESIGN PROPERTIES. INCREASE SIZE, CFMF THICKNESS, OR DECREASE SPACING AS REQUIRED TO SUSTAIN


97 = 0.1017 INCH


- THE DESIGN LOADS. 6. MINIMUM FLANGE WIDTH OF STUD SHAPES SHALL BE 162 = 1-5/8". PROVIDE DOUBLE STUDS AT EACH BEARING END OF COLD-FORMED METAL FRAMING HEADERS, TYPICAL UNLESS NOTED OTHERWISE. CFMF SHALL NOT TERMINATE NEAR FACTORY PUNCH-OUTS A MINIMUM DISTANCE OF 2 x DEPTH.
- 7. COLD-FORMED METAL TRUSS MANUFACTURER SHALL PROVIDE ALL METAL TRUSS HANGERS, WALL ANCHORS AND HURRICANE ANCHORS. 8. THE DESIGN OF PRE-ENGINEERED COLD-FORMED METAL TRUSSES SHALL BE PROVIDED BY THE

COLD-FORMED METAL FRAMING PRODUCT MANUFACTURER. TRUSSES, TRUSS FRAMING

TRUSS-TO-TRUSS CONNECTIONS AND ANCHORAGE SHALL BE DESIGNED BY A PROFESSIONAL

- ENGINEER REGISTERED IN THE STATE OF MICHIGAN. AS A MINIMUM, THE LOADING GIVEN BELOW SHALL BE USED. ADDITIONAL LOADING OR LOAD COMBINATIONS IF REQUIRED BY CODE SHALL BE DETERMINED AND IMPLEMENTED BY THE TRUSS DESIGNER. 9. TRUSS TOP CHORD MUST BE BRACED WITH ROOF SHEATHING AND CONTINUOUS LATERAL BRACING AT MINIMUM 4'-0" O.C. OR AS REQUIRED BY DESIGN. TRUSS BOTTOM CHORD MUST BE BRACED WITH
- CONTINUOUS LATERAL BRACING AT MINIMUM 4'-0" O.C. OR AS REQUIRED BY DESIGN. ALL ROOF SHEATHING PANELS SHALL BE ADHERED AND CONNECTED TO SUPPORTING TRUSSES WITH NO. 8 CORROSION RESISTANT, SELF-DRILLING SCREWS AT 6" O.C. ALONG SUPPORTED EDGES AND AT 12" 10. <u>DESIGN LOADS</u>





STUD WALL DEFLECTION LIMITATIONS SUPPORTING METAL SIDING OR E.I.F.S. -SUPPORTING MASONRY - _____

- SEE PLAN AND/OR

8" MIN - EXTEND LINTEL FOR PLATES

04 00 01 - MASONRY

- 1. THE MASONRY PORTIONS OF THIS STRUCTURE ARE DESIGNED ACCORDING TO THE LATEST WORKING STRESS DESIGN PROVISIONS OF THE MASONRY STANDARDS JOINT COMMITTEE (MSJC) BUILDING CODE REQUIREMENTS FOR MASONRY STRUCTURES (ACI 530/ASCE 5/TMS 402) AND SPECIFICATIONS FOR MASONRY STRUCTURES (ACI 530.1/ASCE 6/TMS 602) INCLUDING SECTIONS 2106 AND 2107 OF CHAPTER 21 IN THE CURRENT BUILDING CODE. MASONRY
- COMPONENTS HAVE BEEN DESIGNED ACCORDING TO THE PROVISIONS FOR SEISMIC DESIGN CATEGORY B.) ALL STRUCTURAL MASONRY IS TO BE CONSTRUCTED IN ACCORDANCE WITH THE LATEST MASONRY STANDARDS JOINT COMMITTEE (MSJC) BUILDING CODE REQUIREMENTS FOR MASONRY STRUCTURES (ACI 530/ASCE 5/TMS 402) AND SPECIFICATIONS FOR MASONRY

ACCORDING TO THE UNIT STRENGTH METHOD FOR CONCRETE MASONRY MSJC SECTION

- STRUCTURES (ACI 530.1/ASCE 6/TMS 602). MASONRY SUBMITTALS ARE REQUIRED BY ACI 530.1/ASCE 6/TMS 602 SECTION 1.5. MASONRY TESTING AND INSPECTIONS ARE REQUIRED BY ACI 530.1/ASCE 6/TMS 602 SECTION 1.6, TABLE 5, LEVEL 2 QUALITY ASSURANCE. 3. ALL STRUCTURAL MASONRY HAS BEEN ENGINEERED IN ACCORDANCE WITH CHAPTER 2, ALLOWABLE STRENGTH DESIGN. COMPRESSION STRENGTH SHALL BE DETERMINED
- 4. ALL BLOCK SHALL CONFORM TO ASTM C 90 AND C 140, TYPE I, GRADE N.

IN CONTACT WITH EARTH_____ TYPE M OR S REINFORCED____ NOT IN CONTACT WITH EARTH TYPE N, M OR S

5. MORTAR SHALL CONFORM TO ASTM C 270, AS FOLLOWS:

TYPE M OR S = 1900 PSI TYPE N = 2150 PSI

FOLLOWS:

6. GROUT SHALL CONFORM TO ASTM C 476, WITH PEA GRAVEL AGGREGATE AND A MINIMUM STRENGTH OF 2,000 PSI. 7. BASED ON THE FOLLOWING MINIMUM STRENGTHS SPECIFIED ABOVE FOR BLOCK, MORTAR AND GROUT, THE MINIMUM COMPOSITE MASONRY COMPRESSIVE STRENGTH, fm, SHALL BE AS

USE	COMPRESSIVE STRENGTH, f'm (PSI)	UNIT STRENGTH (PSI)	GROUT STRENGTH (PSI)	MORTAR TYPE
TYPICAL, U.N.O.	2,000 MIN.	2,800 M I N.	2,000 MIN.	M OR S


- 8. ALL STRUCTURAL MASONRY SHALL COURSE IN STANDARD RUNNING BOND. UNLESS NOTED OTHERWISE, ALL INTERSECTING BEARING WALLS, SHEAR WALLS OR OTHER STRUCTURAL WALLS SHALL BE LAID UP IN INTERLOCKED, BONDED COURSING. MECHANICAL ANCHORS OR WALL TIES MAY BE SUBSTITUTED WITH PRIOR APPROVAL BY THE ENGINEER.
- 9. THE FOLLOWING LAP SPLICE REQUIREMENTS SHALL SUPERCEDE THE CODE REQUIREMENTS. WALL HEIGHTS REFER TO THE DISTANCE FROM THE TOP OF FOUNDATION OR SLAB SUPPORT TO THE UPPER JOIST OR BEAM BEARING OR SLAB/DECK TIE-IN ELEVATION. FOR WALL HEIGHTS EQUALING THE SPECIFIED LIMIT, THE LESSER PROVISION MAY APPLY. AS A MINIMUM, REINFORCING BARS SHALL BE LAPPED ACCORDING TO THE FOLLOWING:

WALL CONFIGURATION	#4 BAR	#5 BAR	#6 BAR	#7 BAR	#8 BAR
8" WALLS (SINGLE REINFORCEMENT)	16"	20"	30"	-	-
8" WALLS (DOUBLE REINFORCEMENT)	16"	26"	38"	-	-
10" WALLS (SINGLE REINFORCEMENT)	16"	16"	24"	32"	42"
10" WALLS (DOUBLE REINFORCEMENT)	16"	26"	38"	54"	-
12" WALLS (SINGLE REINFORCEMENT)	16"	16"	20"	26"	34"
12" WALLS (DOUBLE REINFORCEMENT)	16"	26"	38"	54"	70"
14" WALLS (SINGLE REINFORCEMENT)	16"	16"	16"	22"	28"
14" WALLS (DOUBLE REINFORCEMENT)	16"	26"	38"	54"	70"
16" WALLS (SINGLE REINFORCEMENT)	16"	16"	16"	20"	24"
16" WALLS (DOUBLE REINFORCEMENT)	16"	26"	38"	54"	70"
PROVIDE HORIZONTAL WIRE TYPE RI	- FINEORCING	· · WITH 9 G	AUGE SIDE	RODS ANI	D 9 GALIG


- 10. PROVIDE HORIZONTAL WIRE TYPE REINFORCING WITH 9 GAUGE SIDE RODS AND 9 GAUGE CROSS RODS IN EVERY SECOND COURSE (16" O.C.), IN ALL MASONRY WALLS. SPACE AT 8" O.C AT PARAPET WALLS. PROVIDE "LADDER" TYPE REINFORCING ONLY IN WALLS WITH VERTICAL REINFORCING. PROVIDE ADJUSTABLE TIES AT ALL LINTELS AND CAVITY WALLS AT 16" O.C.
- 10.1. AT MOVEMENT CONTROL JOINTS, INTERRUPT HORIZONTAL JOINT REINFORCING EACH SIDE 11. PROVIDE 1-#5 VERTICAL BAR EACH SIDE OF EACH CONTROL JOINT; SEE PLANS FOR ADDITIONAL
- REINFORCING AT CORNERS, OPENINGS, ETC. 12. ALL REINFORCING BARS, DOWELS AND TIES SHALL CONFORM TO ASTM A615, GRADE 60 VERTICAL REINFORCING BARS SHALL BE HELD IN PLACE BY POSITIONERS SPACED NOT
- FURTHER THAN RECOMMENDED BY CODE 13. PROVIDE A CONTINUOUS BOND BEAM, WITH 2-#5'S, AT THE TOP OF WALLS PARALLEL WITH
- ROOF/FLOOR FRAMING. STEP BOND BEAMS ELEVATIONS AS REQUIRED. STEP IN 8" VERTICAL INCREMENTS AND LAP MINIMUM 32". 13.1. CONTINUE BOND BEAM REINFORCING ACROSS CONTROL JOINTS BUT BREAK GROUT WITH A
- 3/8" SOFT JOINT. STOP ALL BOND BEAM REINFORCING AT BUILDING EXPANSION JOINTS. 14. PERFORM GROUTING ACCORDING TO THE FOLLOWING
- ALL MASONRY BELOW GRADE SHALL BE GROUTED SOLID.
- ALL CORES WITH VERTICAL REINFORCING OR TO RECEIVE DRILLED-IN ANCHORS SHALL BE GROUTED SOLID. ALL MASONRY PIERS AND PILASTERS SHALL BE GROUTED SOLID.
- MAXIMUM 5'-4" (64-INCH) LOW LIFT GROUTING. 15. ALL BEAMS SUPPORTING MASONRY, INCLUDING STEEL, PRECAST AND MASONRY LINTELS ARE TO BEAR 8" (MIN.) ON 3 COURSES (24" DEEP) SOLID MASONRY.
- 16. STRUCTURAL STEEL BEAMS, WIDE FLANGE AND TUBE STEEL LINTELS SHALL BE PROVIDED WITH MIN. 7"x3/8"x0-7" BEARING PLATE, SET 1" AWAY FROM FACE OF WALL, WITH 2-3/4" DIAMETER
- ANCHOR BOLTS EACH END, TYPICAL UNLESS NOTED OTHERWISE. 17. UNLESS NOTED OTHERWISE, PROVIDE LOOSE LINTELS AT MISCELLANEOUS ARCHITECTURAL, MECHANICAL AND ELECTRICAL OPENINGS FOR EACH 4" OF MASONRY WALL THICKNESS IN
 - ACCORDANCE WITH THE FOLLOWING:
- L4x3-1/2x5/16 LLV FOR SPANS UP TO 3'-4" L5x3-1/2x5/16 LLV FOR SPANS UP TO 5'-4"

MISCELLANEOUS OPENINGS

- L6x3-1/2x5/16 LLV FOR SPANS UP TO 6'-8" MAX. AT CONTRACTOR'S OPTION, MASONRY LINTELS ARE ALSO ACCEPTABLE FOR
- 8"W (or 12"w) x 8"H REINF. W/ 2-#5 FOR SPANS UP TO 3'-4" • 8"W (or 12"w) x 8"H REINF. W/ 2-#6 FOR SPANS UP TO 5'-4"
- 8"W (or 12"w) x 16"H REINF. W/ 2-#6 FOR SPANS UP TO 6'-8" MAX.
- COORDINATE REQUIREMENTS FOR LOOSE LINTELS WITH ARCHITECTURAL, MECHANICAL AND ELECTRICAL DRAWINGS.
- ALL STEEL USED FOR LOOSE LINTELS SHALL BE GALVANIZED. 18. ALL DOUBLE ANGLE LINTELS SHALL BE WELDED BACK TO BACK WITH A MINIMUM 2-INCH STITCH WELD EVERY 8-INCHES.





(BOTTOM)



S-020 3/4" = 1'-0"

© COPYRIGHT 2022: ROGVOY ARCHITECTS, P.C





JOISTS

NOTES	:	

LL DEFL L/240 TL DEFL JOIST SPACING

DWG	MARK	QTY	BCX	DESIGNATION	SPAN	SPACE	NU PSF 1	TCX L	TCX R	COMMENTS
	M01	5		20LH07	33'-5"	5.25	10			
	M02	2		28LH05	41'-2"	6'	10			
	M03	14	2	28LH07	41'-2"	6'	10			
	M04	6		28LH07	41'-2"	6'	10			1
	M05	2		18LH02	19'-5"	6'	10			
	M06	4		18LH06	19'-5"	6'	10			
	M07	12		28K7	42'-0"	6'	10			2
	M08	4		28K9	42'-0"	6'	10			2
	M09	26	4	28K8	42'-0"	6'	10			2
	M10	4		28KCS3	42'-0"	6'	10			2
	M11	2		28KCS4	42'-0"	6'	10			2
	M12	6		28K7	42'-0"	6'	10			
	M14	5	1	28K9	42'-0"	6'	10			
	M15	7	1	28K8	42'-0"	6'	10			
	M16	4		28KCS3	42'-0"	6'	10			
	M17	2		28KCS4	42'-0"	6'	10			
	M18	2		28LH05	42'-0"	6'	10			
	M19	14	2	28LH08	42'-0"	6'	10			
	M20	6		28LH08	42'-0"	6'	10			3
	M21	18		28LH06	40'-1"	5.5'	10			
	M22	6	2	28LH06	40'-1"	5.5'	10			4
	M23	3	1	28LH06	40'-1"	5.5'	10			5
	M24	4		28K10	40'-0"	5.5'	10			2
	M25	4		28K7	40'-0"	5.5'	10			2
	M26	29	2	28K6	40'-0"	5.5'	10			2
	M27	8	4	28KCS2	40'-0"	5.5'	10			2
	M28	8		28KCS3	40'-0"	5.5'	10			2
	M29	1		28K9	40'-0"	5.5'	10			2
	TOTAL	208	19							

JOISTS

ſ	NOTES:						0				_
	LL DEFL		240	TL DEFL			•	JO	IST SPACING	0	
DWG	MARK	QTY	BCX	DESIGNATION	SPAN	SPACE	NU PSF	TCX L	TCX R	COMMENTS	
	M30	27	3	28LH06	40'-6"	5.5'	10				
	TOTAL	27	3								

GIRDER

DWG	MARK	QTY	BCX	DESIGNATION	SPAN	NU	TCX L	TCX R	COMMENTS
	G01	2	2	40G7N12.6	41'-10"	2.12			6, 7, 8, 9
	G02	1	1	40G7N11.4	41'-4"	2.12			6, 10, 11
	G03	2	2	40G7N12.1	41'-10"	2.14			6, 7, 12, 13
	G04	2	2	40G7N11	41'-4"	2.14			6, 10, 14
	G05	2	2	40G7N12	41'-10"	2.14			6, 7, 21, 15
	G06	1	1	40G7N12.4	41'-10"	2.14			6, 7, 16, 17
	G07	1	1	40G7N11.3	41'-4"	2.14			6, 10, 18
	G08	1	1	40G7N12.2	41'-10"	2.14			6, 7, 19, 20
	G09	1	1	40G7N9.2	35'-4"	2.03			6, 10, 22, 23
	G10	1	1	40G7N9.7	37'-0"	2.13			6, 10, 24, 25
	G11	1	1	40G7N9.6	37'-0"	2.13			6, 10, 26, 27
	G12	1	1	40G7N9.5	36'-10"	2.13			6, 10, 28, 29
	G14	1	1	40G7N9.0	35'-4"	2.03			6, 10, 30, 31
	G15	2	2	40G7N9.4	37'-0"	2.13			6, 10, 32, 33
	G16	1	1	40G7N9.3	36'-10"	2.13			6, 10, 34, 35
	G17	1	1	40G7N9.6	36'-10"	2.03			6, 10, 36, 37
	G18	2	2	40G7N9.5	37'-0"	2.13			6, 10, 38, 39
	G19	1	1	40G7N9.3	35'-4"	2.13			6, 10, 40, 41
								<u> </u>	
TOTAL		24	24						

NOTES

1	Add'l 0.6K load at 10'-4" & 13'-11" from TE (RTU)	34	Girder designation 40G7N9.3
2	5" deep seat @ TE.	35	ADD'L PL: 6K @ PP1, 1.5K @ PP2. FROM TE
3	Add'l 1.2K load at 3'-0" & 7'-8 1/4" from TE (RTU)	36	ADD'L PL: 5.9K @ PP1, 1.4K @ PP2. FROM TE
4	Add'l 0.6K load at 14'-8" & 19'-2" from TE (RTU)	37	Girder designation 40G7N9.6
5	Add'l 0.6K load at 15'-2" & 19'-8" from TE (RTU)	38	Girder designation 40G7N9.5
6	GIRDER DEFLCETION L/240	39	ADD'L PL: 1.6K @ PP1 & PP2, 0.6K @ PP3 FROM TE
7	JOIST SPACING (6) 5'-9 3/4" & (1) REST OF JOIST SPAN	40	Girder designation 40G7N9.3
8	ADD'L PL: 0.6K @ PP1, 4.7K @ PP6 FROM TE	41	ADD'L PL: 5K @ PP1, 1.1K @ PP2 FROM TE
9	Girder designation 40G7N12.6		
10	JOIST ARE IN EQUAL SPACING		
11	Girder designation 40G7N11.4		
12	ADD'L PL: 0.4K @ PP1, 5.4K @ PP6 FROM TE		
13	Girder designation 40G7N12.1		
14	Girder designation 40G7N11		
15	ADD'L PL: 0.4K @ PP1, 5.6K @ PP6 FROM TE		
16	Girder designation 40G7N12.4		
17	ADD'L PL: 0.9K @ PP2, 4.8K @ PP6 FROM TE		
18	Girder designation 40G7N11.3		
19	Girder designation 40G7N12.2		
20	ADD'L PL: 1.1K @ PP2, 4.8K @ PP6 FROM TE		
21	Girder designation 40G7N12		
22	Girder designation 40G7N9.2		
23	ADD'L PL: 0.4K @ PP1, 0.1K @ PP2, 1.1K @ PP5, 5K @ PP6 FROM TE		
24	Girder designation 40G7N9.7		
25	ADD'L PL: 1.5K @ PP1, 1.4K @ PP2, 0.3K @ PP6 FROM TE		
26	Girder designation 40G7N9.6		
27	ADD'L PL: 1.5K @ PP1 & PP2, 0.2K @ PP3 FROM TE		
28	Girder designation 40G7N9.5		
29	ADD'L PL: 0.2K @ PP1, 0.5K @ PP2 & 0.2K @ PP3 FROM TE		
30	Girder designation 40G7N9		
31	ADD'L PL: 5.2K @ PP1, 1.2K @ PP2. FROM TE		
32	Girder designation 40G7N9.4		
33	ADD'L PL: 0.5K @ PP1, 0.5K @ PP2. FROM TE		